



# LED High Bay Light

## AML® HB series

**Light type:**

round design LED High Bay Light for suspended 1-point mounting

**Area of application:**

industrial spaces, workshops, high warehouses, offices/commercial spaces, lofts, swimming pool, petrol stations, outdoor areas under roof

**Light efficiency:**

up to 120 lm/w

- Lumileds LED chip, LUXEON 3030 2D
- quality LED drivers Mean Well (HLG-series)
- flicker free and healthy light
- average life span L80 (tq 25 °C): 50,000h
- 3 in 1 dimming (resistor, PWM or 1-10VDC)
- input voltage: 90-305V
- certification: CE, TÜV, RoHS
- robust aluminum die-cast housing in polished silver
- operating temperature: -40 °C to +80 °C
- suitable for wet rooms, covered outdoor use
- IP 54 classified (complete protection against dust and water spray)
- installation with commercially available chain, cable or threaded rod
- ca. 120 cm connection cable, screwed steel eye (M20), operating instruction included

**warranty: 5 years**

**availability guarantee: 10 years**



Type	AML-HB-100 D	AML-HB-120 D	AML-HB-150 D	AML-HB-200 D	AML-HB-250 D
<b>Wattage</b>	100 watts	120 watts	150 watts	200 watts	250 watts
<b>Luminous flux</b>	12.000lm	14.400m	18.000lm	24.000lm	30.000lm
<b>Color temperature</b>	4.000K (neutral white) / special order: 2.700K (warm white) / 5.700K (daylight white)				
<b>Beam angle</b>	120° / special order: 60° / 90°				
<b>Weight</b>	4,1 kg	4,1 kg	4,6 kg	5,9 kg	5,9 kg
<b>Dimension (mm)</b>	Ø492X354	Ø492X354	Ø492X404	Ø492X429	Ø492X429

Please refer to our price list for order numbers/EAN-Codes.