



## LED Tubes

### AML® T8 ECO series

**Light type:**

LED Tubes for replacement of conventional fluorescent tubes

**Area of application:**

industrial spaces, workshops, high warehouses, offices / commercial spaces, lofts, swimming pool, petrol station

**Light efficiency:**

up to 140 lm/W



- quality LED Chips Epistar SMD 2835
- average life span L80 (tq 25 °C): 50,000 h
- Input Voltage: 185-265V
- Certification: CE, RoHS
- Robust glass body
- Operating temperature: -40 °C – +85 °C
- no flicker and healthy light
- IP 20 classified (protected against solid foreign bodies with diameter > 12,55mm)
- mercury-free
- CRI: >80
- flicker-free instant start
- 3 pieces per packaging unit including 3 starters

**warranty: 3 years**

Typ	AML-T8-60 ECO	AML-T8-90 ECO	AML-T8-120 ECO	AML-T8-150 ECO
wattage	9 Watt	12 Watt	18 Watt	22 Watt
luminous flux	1.260 lm	1.680 lm	2.520 lm	3.080 lm
color temperature	4.000K (neutral white)			
beam angle	330°			
weight	0,15 kg	0,20 kg	0,35 kg	0,40 kg
dimension (mm)	600XØ26	900XØ26	1200XØ26	1500XØ26

Please refer to our price list for order numbers/EAN codes.