



LED floodlight

AML® FL series

Light type:

Design LED outdoor floodlight

Area of application:

industrial spaces, workshops, high warehouses, offices / commercial spaces, outdoor areas such as car parks or courtyards, as accent lightning

Light efficiency:

90 lm/W



- quality LED Chips Epistar 2835
- Average life span L80 (tq 25 °C): 50,000 h
- Input Voltage: 90-265V
- Certification: CE, RoHS
- Robust aluminium die-cast housing
- Modern and high-quality design in pure white or black
- Operating temperature: -20 °C – +60 °C
- Suitable for indoors and outdoors
- IP 65 classified (complete protection against dust and water jets from all directions)
- With 360° metal clamp for stable mounting
- 120cm connection cable (3-pole), metal clamp and German manual included



Warranty: 5 years

availability guarantee: 10 years

typ	AML-FL-10	AML-FL-20	AML-FL-30	AML-FL-50
Wattage	10 Watt	20 Watt	30 Watt	50 Watt
luminous flux	900lm	1.800lm	2.700lm	4.500lm
color temperature	4.000K (neutral white) / special order: 2.700K (warm white) / 5.000K (daylight white)			
beam angle	110°			
weight	0,50 kg	0,9 kg	1,50 kg	1,90 kg
dimension (mm)	139x136x25	195x191x32	239x236x40	255x276x40

Please refer to our price list for order numbers/EAN codes..