



## LED street light

### AML® SL2 series

#### Light type:

long-lasting street lights for use in industry and municipalities

#### Area of application:

roads, paths, parking lots, construction sites, petrol stations, riding arenas and much more

#### Light efficiency:

up to 166 lm/W



- branded LED Chips Lumileds LUXEON 5050
- quality LED drivers Mean Well (HLG-series)
- flicker free and healthy light, certified according to the IEEE 1789-2015 norm
- Average life span L80 (tq 25 °C): 50,000 h
- Input Voltage: 100-277V
- Certification: CE, TÜV, RoHS,
- Robust aluminium die-cast housing in black in light gray
- Operating temperature: -40 °C – +80 °C
- Suitable for indoors and outdoors
- IP 65 classified (complete protection against dust and water jets from all directions)
- Spigot 60mm (one screw on 60mm round tube)
- Multiple locking, connecting cable is inserted through round tube
- optional mounting bracket, 180° (AML® SI2-B)

**warranty: 3 Jahre**

| type            | AML-SL2-50  | AML-SL2-75 | AML-SL2-150 | AML-SL2-200 |
|-----------------|---|------------|-------------|-------------|
| wattage         | 50 Watt   | 75 Watt    | 150 Watt    | 200 Watt    |
| light output    | 7.500lm   | 11.250lm   | 24.900lm    | 33.200lm    |
| light colour    | 4.000K (neutral white) / Special order: 3.000K (warm white) / 5.000K (daylight white) |            |             |             |
| beam angle      | 110x155°  | 65x140°    | 65x140°     | 65x140°     |
| weight          | 1,9 kg  | 3,1 kg     | 4,4 kg      | 4,5 kg      |
| dimensions (mm) | 430x200x70  | 500x250x45 | 650x334x119 | 650x334x119 |

Please refer to our price list for the order numbers/EAN codes.