



LED street light

AML® SL2 series

Light type:

long-lasting street lights for use in industry and municipalities

Area of application:

roads, paths, parking lots, construction sites, petrol stations, riding arenas and much more

Light efficiency:

up to 166 lm/W



- branded LED Chips Lumileds LUXEON 5050
- quality LED drivers Mean Well (HLG-series)
- flicker free and healthy light, certified according to the IEEE 1789-2015 norm
- Average life span L80 (tq 25 °C): 50,000 h
- Input Voltage: 100-277V
- Certification: CE, TÜV, RoHS,
- Robust aluminium die-cast housing in black in light gray
- Operating temperature: -40 °C – +80 °C
- Suitable for indoors and outdoors
- IP 65 classified (complete protection against dust and water jets from all directions)
- Spigot 60mm (one screw on 60mm round tube)
- Multiple locking, connecting cable is inserted through round tube
- optional mounting bracket, 180° (AML® SL2-B)

warranty: 3 Jahre

| type | AML-SL2-50 | AML-SL2-75 | AML-SL2-150 |
|-----------------|---|------------|-------------|
| wattage | 50 Watt | 75 Watt | 150 Watt |
| light output | 7.500lm | 11.250lm | 24.900lm |
| light colour | 4.000K (neutral white) / special order: 3.000K (warm white) / 5.000K (daylight white) | | |
| beam angle | 110x155° | 65x140° | 65x140° |
| weight | 1,9 kg | 3,1 kg | 3,9 kg |
| dimensions (mm) | 400x200x70 | 500x250x45 | 650x300x80 |

Please refer to our price list for order numbers/EAN codes.